

Specifications



MODEL	RXQ215ARY6B		RXQ430ARY6B		RXQ645ARY6B	
Combination Units	-		RXQ215ARY6B		RXQ215ARY6B	
	-		RXQ215ARY6B		RXYQ215TRY6B	
	-		-		RXQ215ARY6B	
Power Supply	3-Phase, 380-415 V, 50Hz					
Cooling Capacity	Btu/h	204,700	409,400	614,100		
	kW	60	120	180		
Power Input (Cooling)	kW	19.7	39.4	59.1		
C.O.P (Cooling)	-	3.05	3.05	3.05		
Capacity Control	%	50-130	50-130	50-120		
Casing Colour	Ivory white (5Y7.5/1)					
Compressor	Type	Hermetically Sealed Scroll Type				
	No. of compressor	2	4	6		
Airflow Rate	m ³ /min	297	594	891		
Dimensions (HXWXD)	mm	1,657X1,240X765	(1,657X1,240X765)+ (1,657X1,240X765)	(1,657X1,240X765)+ (1,657X1,240X765)+ (1,657X1,240X765)		
Machine weight	Kg	285	285+285	285+285+285		
Sound level	dB(A)	65	68	70		
Operation Range	Cooling	°CDB		10 to ~49	10 to ~49	10 to ~49
	Type	R410A				
Refrigerant	Charge	Kg	11.8	11.8+11.8	11.8+11.8+11.8	
	Piping connections	Liquid	mm	φ 15.9 (Brazing)	φ 19.1 (Brazing)	φ 19.1 (Brazing)
		Gas	mm	φ 28.6 (Brazing)	φ 41.3 (Brazing)	41.3 (Brazing)

Optional Accessories		RXQ215ARY6B
Disinbutive piping	REFNET header	KHRP26M22H, KHRP26M33H, KHRP26M72H (Max.4 branch) (Max.8 branch) (Max.8 branch)
	REFNET joint	KHRP26A22T, KHRP26A33T, KHRP26A72T

Optional Accessories		RXQ430ARY6B
Disinbutive piping	REFNET header	KHRP26M22H, KHRP26M33H, KHRP26M72H, KHRP26M73H (Max.4 branch) (Max.8 branch) (Max.8 branch) (Max.8 branch)
	REFNET joint	KHRP26A22T, KHRP26A33T, KHRP26A72T, KHRP26A73T
Pipe size reducer		KHRP26M73TP, KHRP26M73HP
Outdoor unit connection piping kit		BHFP22P100

Optional Accessories		RXQ645ARY6B
Disinbutive piping	REFNET header	KHRP26M22H, KHRP26M33H, KHRP26M72H, KHRP26M73H (Max.4 branch) (Max.8 branch) (Max.8 branch) (Max.8 branch)
	REFNET joint	KHRP26A22T, KHRP26A33T, KHRP26A72T, KHRP26A73T
Pipe size reducer		KHRP26M73TP, KHRP26M73HP
Outdoor unit connection piping kit		BHFP22P151